

Org-Mode Reference Card (1/2)

(for version 4.21)

Getting Started

(add-to-list 'auto-mode-alist '(("\\.org\$" . org-mode))
(define-key global-map "\C-cl" 'org-store-link)²
(define-key global-map "\C-ca" 'org-agenda)²

For the many customization options try M-x org-customize
To read the on-line documentation try M-x org-info

Visibility Cycling

rotate current subtree between states TAB
rotate entire buffer between states S-TAB
show the whole file C-c C-a

Motion

next heading C-c C-n
previous heading C-c C-p
next heading, same level C-c C-f
previous heading, same level C-c C-b
backward to higher level heading C-c C-u
jump to another place in document C-c C-j

Structure Editing

insert new heading/item at current level M-RET
insert new TODO entry M-S-RET
promote current heading up one level M-LEFT
demote current heading down one level M-RIGHT
promote current subtree up one level M-S-LEFT
demote current subtree down one level M-S-RIGHT
move subtree/list item up M-S-UP
move subtree/list item down M-S-DOWN
kill subtree C-c C-x C-w
copy subtree C-c C-x M-w
yank subtree C-c C-x C-y
archive subtree C-c \$
To set archive location for current file, add a line like³:
#+ARCHIVE: archive::* Archived Tasks

Filtering and Sparse Trees

show sparse tree for all matches of a regexp C-c /
view TODO's in sparse tree C-c C-v
global TODO list in agenda mode C-c t²
create sparse tree with all deadlines due C-c C-w
time sorted view of current org file C-c C-r

Tags

set tags for current heading C-c C-c
realign tags in all headings C-u C-c C-c
create sparse tree with matching tags C-c \
globally (agenda) match tags at cursor C-c C-o

TODO Items

rotate the state of the current item C-c C-t
view TODO items in a sparse tree C-c C-v
view 3rd TODO keyword's sparse tree C-3 C-c C-v

set the priority of the current item C-c , [ABC]
remove priority cookie from current item C-c , SPC
raise priority of current item S-UP⁴
lower priority of current item S-DOWN⁴

todo workflow #+SEQ_TODO: TODO TRY BLUFF DONE
todo types #+TYP_TODO: Phil home work DONE

Timestamps

prompt for date and insert timestamp C-c .
like C-c . but insert date and time format C-u C-c .
Like C-c . but make stamp inactive C-c !
insert DEADLINE timestamp C-c C-d
insert SCHEDULED timestamp C-c C-s
create sparse tree with all deadlines due C-c C-w
the time between 2 dates in a time range C-c C-y
change timestamp at cursor by ±1 day S-RIGHT/LEFT⁴
change year/month/day at cursor by ±1 S-UP/DOWN⁴
access the calendar for the current date C-c >
insert timestamp matching date in calendar C-c <
access agenda for current date C-c C-o
Select date while prompted mouse-1/RET

Links

globally store link to the current location C-c l²
insert a link (TAB completes stored links) C-c C-1
insert file link with file name completion C-u C-c C-1
edit (also hidden part of) link at point C-c C-1
open file links in emacs (C-u : in emacs) C-c C-o
open link at point (3: in emacs) mouse-2/3
record a position in mark ring C-c %
jump back to last followed link(s) C-c &

Internal Links

<<My Target>> target
<<<My Target>>> radio target³
[[*this text]] find headline
[[this text]] find target or text in buffer
[[this text][description]] optional link text

External Links

file:/home/dominik/img/mars.jpg file, absolute
file:papers/last.pdf file, relative
file:projects.org:*that text find headline
file:projects.org::find me find tgt/string
file:projects.org::/regexp/ regexp search
http://www.astro.uva.nl/~dominik on the web
mailto:adent@galaxy.net EMail address
news:comp.emacs Usenet group
bbdb:Richard Stallman BBDB person
shell:ls *.org shell command
gnus:group GNUS group
gnus:group#id GNUS message
vm|wl|mhe|rmail:folder Mail folder
vm|wl|mhe|rmail:folder#id Mail message
[[external link][description]] optional link text

Tables

Creating a table

just start typing, e.g. |Name|Phone|Age RET | - TAB
convert region to table C-c |
... separator at least 3 spaces C-3 C-c |

Commands available inside tables

The following commands work when the cursor is *inside a table*.
Outside of tables, the same keys may have other functionality.

Re-aligning and field motion

re-align the table without moving the cursor C-c C-c
re-align the table, move to next field TAB
move to previous field S-TAB
re-align the table, move to next row RET

Row and column editing

move the current column left M-LEFT
move the current column right M-RIGHT
kill the current column M-S-LEFT
insert new column to left of cursor position M-S-RIGHT
move the current row up M-UP
move the current row down M-DOWN
kill the current row or horizontal line M-S-UP
insert new row above the current row M-S-DOWN
insert horizontal line below the current row C-c -
insert horizontal line above the current row C-u C-c -
sort lines in region C-c ^

Regions

cut rectangular region C-c C-x C-w
copy rectangular region C-c C-x M-w
paste rectangular region C-c C-x C-y
fill paragraph across selected cells C-c C-q

Calculations (in combination with Emacs calc package)

set and eval column formula C-c =
set and eval named-field formula C-u C-c =
edit formulas in separate buffer C-c '
re-apply all stored equations to current line C-c *
re-apply all stored equations to entire table C-u C-c *
rotate calculation mark through # * ! ^ _ \$ C-#
display column number cursor is in C-c ?
sum numbers in current column/rectangle C-c +
copy down with increment S-RET⁴

Formulas typed in field are executed by TAB, RET and C-c C-c.
= introduces a column formula, := a named-field formula.

Example: Add Col1 and Col2 = \$1+\$2
... with printf format specification = \$1+\$2;%,2f
... with constants from constants.el = \$1/\$c/\$cm
:= vsum(&IIII) : = vsum(&IIII)
=

Miscellaneous

to limit column width to N characters, use ... | <N> | ...
edit the current field in a separate window C-c '
make current field fully visible C-u TAB
export as tab-separated file M-x org-table-export
import tab-separated file M-x org-table-import

Tables created with the table.el package

insert a new table.el table C-c ~
recognize existing table.el table C-c C-c
convert table (Org-mode ↔ table.el) C-c ~

Org-Mode Reference Card (2/2)

(for version 4.21)

Agenda Views

add/move current file to front of agenda	C-c [
remove current file from your agenda	C-c]
cycle through agenda file list	C-,
compile agenda for the current week	C-c a a ²
compile global TODO list	C-c a t ²
compile TODO list for specific keyword	C-c a T ²
match tags in agenda files	C-c a m ²
agenda for date at cursor	C-c C-o
show timeline of current org file	C-c C-r

To set categories, add lines like³:

```
#+CATEGORY: MyCateg
```

Commands available in an agenda buffer

View Org file

show original location of item	SPC
... also available with	mouse-3
show and recenter window	L
goto original location in other window	TAB
... also available with	mouse-2
goto original location, delete other windows	RET
toggle follow-mode	f

Change display

delete other windows	o
switch to daily / weekly view	d / w
toggle inclusion of diary entries	D
toggle time grid for daily schedule	g
toggle display of logbook entries	l
refresh agenda buffer with any changes	r
display the following org-agenda-ndays	RIGHT
display the previous org-agenda-ndays	LEFT
goto today	.

Remote editing

digit argument	0-9
change state of current TODO item	t
show tags of current headline	T
set tags for current headline	:
set priority of current item	p
raise/lower priority of current item	S-UP/DOWN ⁴
display weighted priority of current item	P
change timestamp to one day earlier/later	S-LEFT/RIGHT ⁴
change timestamp to today	>
insert new entry into diary	i

Calendar commands

find agenda cursor date in calendar	c
compute agenda for calendar cursor date	c
show phases of the moon	M
show sunrise/sunset times	S
show holidays	H
convert date to other calendars	C

Quit and Exit

quit agenda, remove agenda buffer	q
exit agenda, remove all agenda buffers	x

Exporting

Exporting creates files with extensions *.txt* and *.html* in the current directory.

export as ASCII file	C-c C-x a
export visible text only (e.g. for printing)	C-c C-x v
export as HTML file	C-c C-x h
export as HTML and open in browser	C-c C-x b
prefix arg sets nb. of headline levels, e.g.	C-3 C-c C-x h
export as iCalendar file	C-c C-x i
export all agenda files as iCalendar files	C-c C-x C-i
combine all agenda files to single iCal file	C-c C-x C-c
insert template of export options	C-c C-x t
toggle fixed width for entry or region	C-c :

HTML formatting

make words bold	*bold*
make words <i>italic</i>	/italic/
make words <u>underlined</u>	_underlined_
sub- and superscripts	x ^{^3} , J _{dust}
TeX-like macros	\alpha, \to
typeset lines in fixed width font	start with :
tables are exported as HTML tables	start with
links become HTML links	http:... etc
include html tags	@...@

Export options

Include additional information for export by putting these anywhere in the org file. Use M-TAB completion to make sure to get the right keywords. M-TAB again just after keyword is complete inserts examples.

the title to be shown	#+TITLE:
the author	#+AUTHOR:
authors email address	#+EMAIL:
language code for html	#+LANGUAGE:
free text description of file	#+TEXT:
... which can carry over multiple lines	#+TEXT:
settings for the export process - see below	#+OPTIONS:

Settings for the OPTIONS line

set number of headline levels for export	H:2
turn on/off section numbers	num:t
turn on/off table of contents	toc:t
turn on/off linebreak preservation	\n:nil
turn on/off quoted html tags	@:t
turn on/off fixed width sections	::t
turn on/off tables	:t
turn on/off TeX syntax for sub/super-scripts	^:t
turn on/off emphasised text	*:nil
turn on/off TeX macros	TeX:t

Comments: Text not being exported

Text before the first headline is not considered part of the document and is therefore never exported. Lines starting with # are comments and are not exported. Subtrees whose header starts with COMMENT are never exported.

toggle COMMENT keyword on entry	C-c ;
---------------------------------	-------

Completion

In-buffer completion completes TODO keywords at headline start, TeX macros after “\”, option keywords after “#-”, TAGS after “:”, and dictionary words elsewhere.

Complete word at point	M-TAB
------------------------	-------

Calendar and Diary Integration

To include entries from the Emacs diary in your Org-mode agenda:

```
(setq org-agenda-include-diary t)
```

To include the Org-mode agenda in the normal diary, make sure you're using the fancy diary display and in the ~/diary file add

```
&%(org-diary)
```

to include all the files listed in org-agenda-files. For more selective file inclusion use a line for each file:

```
&%(org-diary) ~/path/to/some/org-file.org
```

Remember-mode Integration

See the manual for how to make remember.el use Org-mode links and files. The note-finishing command C-c C-c will first prompt for an org file. In the file, find a location with:

rotate subtree visibility	TAB
next heading	DOWN
previous heading	UP

Insert the note with one of the following:

as sublevel of heading at cursor	RET
right here (cursor not on heading)	RET
before current heading	LEFT
after current heading	RIGHT
shortcut to end of buffer (cursor at buf-start)	RET
Abort	q

CUA and pc-select compatibility

Configure the variable org-CUA-compatibility to make Org-mode avoid the S-<cursor> bindings used by these modes. When set, Org-mode will change the following keybindings (also in the agenda buffer, but not during date selection). See note mark four⁴ throughout the reference card.

S-UP	→ M-p	S-DOWN	→ M-n
S-LEFT	→ M--	S-RIGHT	→ M++
S-RET	→ C-S-RET		

Notes

¹ The six autoload forms are only needed if Org-mode is not part of Emacs, or an XEmacs package.

² This is only a suggestion for a binding of this command. Choose you own key as shown under INSTALLATION.

³ After changing a #+KEYWORD or <<<target>>> line, press C-c C-c with the cursor still in the line to update.

⁴ Keybinding affected by org-CUA-compatibility.

Copyright © 2006 Free Software Foundation, Inc.
v4.21 for Org-Mode 4.21, 2006

Author: Philip Rooke
based on refcard design and format by Stephen Gildea

Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.