

# g Org-Mode Reference Card (1/2)

(for version 4.45)

## Getting Started

```
(add-to-list 'auto-mode-alist '(("\\.org$" . org-mode))
(define-key global-map "\C-cl" 'org-store-link)1
(define-key global-map "\C-ca" 'org-agenda)1
```

For the many customization options try `M-x org-customize`  
To read the on-line documentation try `M-x org-info`

## Visibility Cycling

rotate current subtree between states `TAB`  
rotate entire buffer between states `S-TAB`  
show the whole file `C-c C-a`

## Motion

next/previous heading `C-c C-n/p`  
next/previous heading, same level `C-c C-f/b`  
backward to higher level heading `C-c C-u`  
jump to another place in document `C-c C-j`  
previous/next plain list item `S-UP/DOWN`<sup>3</sup>

## Structure Editing

insert new heading/item at current level `M-RET`  
insert new TODO entry/checkbox item `M-S-RET`  
promote current heading up one level `M-LEFT`  
demote current heading down one level `M-RIGHT`  
promote current subtree up one level `M-S-LEFT`  
demote current subtree down one level `M-S-RIGHT`  
move subtree/list item up/down `M-S-UP/DOWN`  
kill subtree `C-c C-x C-w`  
copy subtree `C-c C-x M-w`  
yank subtree `C-c C-x C-y`  
narrow buffer to current subtree `C-x n s`

## Archiving

toggle ARCHIVE tag `C-c C-x C-a`  
mark fully done children `C-u C-c C-x C-a`  
force cycling of an ARCHIVED tree `C-TAB`  
move subtree to archive file `C-c $`  
move all fully done children `C-u C-c $`  
To set archive location for current file, add a line like<sup>2</sup>:  
`#+ARCHIVE: archive::* Archived Tasks`

## Filtering and Sparse Trees

show sparse tree for all matches of a regexp `C-c /`  
view TODO's in sparse tree `C-c C-v`  
global TODO list in agenda mode `C-c t`<sup>1</sup>  
create sparse tree with all deadlines due `C-c C-w`  
time sorted view of current org file `C-c a L`

## Tables

### Creating a table

just start typing, e.g. `|Name|Phone|Age RET |-` TAB  
convert region to table `C-c |`  
... separator at least 3 spaces `C-3 C-c |`

### Commands available inside tables

The following commands work when the cursor is *inside a table*.  
Outside of tables, the same keys may have other functionality.

### Re-aligning and field motion

re-align the table without moving the cursor `C-c C-c`  
re-align the table, move to next field `TAB`  
move to previous field `S-TAB`  
re-align the table, move to next row `RET`

### Row and column editing

move the current column left `M-LEFT`  
move the current column right `M-RIGHT`  
kill the current column `M-S-LEFT`  
insert new column to left of cursor position `M-S-RIGHT`  
move the current row up `M-UP`  
move the current row down `M-DOWN`  
kill the current row or horizontal line `M-S-UP`  
insert new row above the current row `M-S-DOWN`  
insert horizontal line below the current row `C-c -`  
insert horizontal line above the current row `C-u C-c -`  
sort lines in region `C-c ^`

### Regions

cut rectangular region `C-c C-x C-w`  
copy rectangular region `C-c C-x M-w`  
paste rectangular region `C-c C-x C-y`  
fill paragraph across selected cells `C-c C-q`

### Calculations (in combination with Emacs calc package)

set and eval column formula `C-c =`  
set and eval named-field formula `C-u C-c =`  
edit formulas in separate buffer `C-c '`  
re-apply all stored equations to current line `C-c *`  
re-apply all stored equations to entire table `C-u C-c *`  
rotate calculation mark through `# * ! ^ _ $` `C-#`  
display column number cursor is in `C-c ?`  
sum numbers in current column/rectangle `C-c +`  
copy down with increment `S-RET`<sup>3</sup>

Formulas typed in field are executed by TAB, RET and C-c C-c.  
= introduces a column formula, := a named-field formula.

Example: Add Col1 and Col2 `=$1+$2`  
... with printf format specification `=$1+$2;%.2f`  
... with constants from constants.el `=$1/$c/$cm`  
sum from 3rd hline above to here `:=vsum(&III)`  
apply current column formula `=`

### Miscellaneous

to limit column width to N characters, use `...| <N> |...`  
edit the current field in a separate window `C-c '`  
make current field fully visible `C-u TAB`  
export as tab-separated file `M-x org-table-export`  
import tab-separated file `M-x org-table-import`

### Tables created with the table.el package

insert a new `table.el` table `C-c ~`  
recognize existing `table.el` table `C-c C-c`  
convert table (Org-mode ↔ `table.el`) `C-c ~`

## Links

globally store link to the current location `C-c l`<sup>1</sup>  
insert a link (TAB completes stored links) `C-c C-l`  
insert file link with file name completion `C-u C-c C-l`  
edit (also hidden part of) link at point `C-c C-l`  
open file links in emacs (`C-u` : in emacs) `C-c C-o`  
open link at point (3: in emacs) `mouse-2/3`  
jump back to last followed link(s) `C-c &`

### Internal Links

<<My Target>> target  
<<<My Target>>> radio target<sup>2</sup>  
[[\*this text]] find headline  
[[this text]] find target or text in buffer  
[[this text][description]] optional link text

### External Links

file:/home/dominik/img/mars.jpg file, absolute  
file:papers/last.pdf file, relative  
file:projects.org:\*that text find headline  
file:projects.org::find me find trgt/string  
http://www.astro.uva.nl/~dominik on the web  
mailto:adent@galaxy.net Email address  
news:comp.emacs Usenet group  
bbdb:Richard Stallman BBDB person  
gnus:group GNUS group  
gnus:group#id GNUS message  
vm|wl|mhe|rmail:folder Mail folder  
vm|wl|mhe|rmail:folder#id Mail message  
info:emacs:Regexps Info file:node  
shell:ls \*.org shell command  
elisp:(calendar) elisp form  
[[external link][description]] optional link text

## Remember-mode Integration

See the manual for how to make remember.el use Org-mode links and files. The note-finishing command `C-c C-c` will first prompt for an org file. In the file, find a location with:

rotate subtree visibility `TAB`  
next heading `DOWN`  
previous heading `UP`

Insert the note with one of the following:

as sublevel of heading at cursor `RET`  
right here (cursor not on heading) `RET`  
before current heading `LEFT`  
after current heading `RIGHT`  
shortcut to end of buffer (cursor at buf-start) `RET`  
Abort `q`

## Completion

In-buffer completion completes TODO keywords at headline start, TeX macros after “\”, option keywords after “#-”, TAGS after “:”, and dictionary words elsewhere.

Complete word at point `M-TAB`

# Org-Mode Reference Card (2/2)

(for version 4.45)

## TODO Items and Checkboxes

rotate the state of the current item	C-c C-t
view TODO items in a sparse tree	C-c C-v
view 3rd TODO keyword's sparse tree	C-3 C-c C-v
set the priority of the current item	C-c , [ABC]
remove priority cookie from current item	C-c , SPC
raise priority of current item	S-UP <sup>3</sup>
lower priority of current item	S-DOWN <sup>3</sup>
#+SEQ_TODO: TODO TRY BLUFF DONE	todo workflow
#+TYP_TODO: Phil home work DONE	todo types
insert new checkbox item in plain list	M-S-RET
toggle checkbox(es) in region/entry/at point	C-c C-x C-b
toggle checkbox at point	C-c C-c
checkbox statistics cookies: insert [/] or [%]	
update checkbox statistics (C-u : whole file)	C-c #

## Tags

set tags for current heading	C-c C-c
realign tags in all headings	C-u C-c C-c
create sparse tree with matching tags	C-c \
globally (agenda) match tags at cursor	C-c C-o

## Timestamps

prompt for date and insert timestamp	C-c .
like C-c . but insert date and time format	C-u C-c .
Like C-c . but make stamp inactive	C-c !
insert DEADLINE timestamp	C-c C-d
insert SCHEDULED timestamp	C-c C-s
create sparse tree with all deadlines due the time between 2 dates in a time range	C-c C-w
change timestamp at cursor by ±1 day	C-c C-y
change year/month/day at cursor by ±1	S-RIGHT/LEFT <sup>3</sup>
access the calendar for the current date	S-UP/DOWN <sup>3</sup>
insert timestamp matching date in calendar	C-c >
access agenda for current date	C-c <
Select date while prompted	C-c C-o
	mouse-1/RET

## Clocking Time

start clock on current item	C-c C-x C-i
stop clock on current item	C-c C-x C-o
cancel current clock	C-c C-x C-x
display total subtree times	C-c C-x C-d
remove displayed times	C-c C-c
insert/update table with clock report	C-c C-x C-r

## LaTeX and cldatex-mode

preview LaTeX fragment	C-c C-x C-1
Expand abbreviation (cldatex-mode)	TAB
Insert/modify math symbol (cldatex-mode)	' / '

## Agenda Views

add/move current file to front of agenda	C-c [
remove current file from your agenda	C-c ]
cycle through agenda file list	C-,
compile agenda for the current week	C-c a a <sup>1</sup>
compile global TODO list	C-c a t <sup>1</sup>
compile TODO list for specific keyword	C-c a T <sup>1</sup>
match tags in agenda files	C-c a m <sup>1</sup>
match tags in TODO entries	C-c a M <sup>1</sup>
show timeline of current org file	C-c a L <sup>1</sup>
agenda for date at cursor	C-c C-o
configure custom commands	C-c a C <sup>1</sup>

To set categories, add lines like<sup>2</sup>:  
#+CATEGORY: MyCateg

### Commands available in an agenda buffer

#### View Org file

show original location of item	SPC
... also available with	mouse-3
show and recenter window	L
goto original location in other window	TAB
... also available with	mouse-2
goto original location, delete other windows	RET
toggle follow-mode	f

#### Change display

delete other windows	o
switch to daily / weekly view	d / w
toggle inclusion of diary entries	D
toggle time grid for daily schedule	g
toggle display of logbook entries	l
refresh agenda buffer with any changes	r
save all org-mode buffers	s
display the following org-agenda-ndays	RIGHT
display the previous org-agenda-ndays	LEFT
goto today	.

#### Remote editing

digit argument	0-9
change state of current TODO item	t
show tags of current headline	T
set tags for current headline	:
toggle ARCHIVE tag	a
set priority of current item	p
raise/lower priority of current item	S-UP/DOWN <sup>3</sup>
display weighted priority of current item	P
schedule/set deadline for this item	C-c C-s/d
change timestamp to one day earlier/later	S-LEFT/RIGHT <sup>3</sup>
change timestamp to today	>
insert new entry into diary	i
Start the clock on current item (clock-in)	I
Stop the clock (clock-out)	O
Cancel current clock	X

#### Calendar commands

find agenda cursor date in calendar	c
compute agenda for calendar cursor date	c
show phases of the moon	M
show sunrise/sunset times	S
show holidays	H
convert date to other calendars	C

#### Quit and Exit

quit agenda, remove agenda buffer	q
exit agenda, remove all agenda buffers	x

## Calendar and Diary Integration

Include Emacs diary entries into Org-mode agenda with:  
(setq org-agenda-include-diary t)

## Exporting and Publishing

Exporting creates files with extensions *.txt* and *.html* in the current directory. Publishing puts the resulting file into some other place.

export/publish dispatcher	C-c C-e
export visible part only	C-c C-e v
insert template of export options	C-c C-x t
toggle fixed width for entry or region	C-c :

### HTML formatting

make words <b>bold</b>	*bold*
make words <i>italic</i>	/italic/
make words <u>underlined</u>	_underlined_
sub- and superscripts	x <sup>^3</sup> , J <sub>dust</sub>
T <sub>E</sub> X-like macros	\alpha, \to
typeset lines in fixed width font	start with
tables are exported as HTML tables	start with
links become HTML links	http:... etc
include html tags	@<b>...@</b>

### Export options

Include additional information for export by putting these anywhere in the org file. Use M-TAB completion to make sure to get the right keywords. M-TAB again just after keyword is complete inserts examples.

the title to be shown	#+TITLE:
the author	#+AUTHOR:
authors email address	#+EMAIL:
language code for html	#+LANGUAGE:
free text description of file	#+TEXT:
... which can carry over multiple lines	#+TEXT:
settings for the export process	#+OPTIONS:

### Comments: Text not being exported

Text before the first headline is not considered part of the document and is therefore never exported. Lines starting with # are comments and are not exported. Subtrees whose header starts with COMMENT are never exported.

toggle COMMENT keyword on entry	C-c ;
---------------------------------	-------

## Dynamic Blocks

update dynamic block at point	C-c C-x C-u
update all dynamic blocks	C-u C-c C-x C-u

## Notes

<sup>1</sup> This is only a suggestion for a binding of this command. Choose you own key as shown under INSTALLATION.

<sup>2</sup> After changing a #+KEYWORD or <<<target>>> line, press C-c C-c with the cursor still in the line to update.

<sup>3</sup> Keybinding affected by org-CUA-compatibility.

Copyright © 2006 Free Software Foundation, Inc.  
v4.45 for Org-Mode 4.45, 2006  
Author: Philip Rooke

based on refcard design and format by Stephen Gildea

Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.